




ENVIRONMENTAL PRODUCT DECLARATION

larson pe[®]-larson fr[®]

PANEL COMPOSITE DE ALUMINIO PARA ARQUITECTURA, APLICACIONES DE IMAGEN CORPORATIVA, SECTORES AUTOMOCIÓN Y NAVAL, ENTRE OTROS



larson pe[®] larson fr[®]



ACCORDING TO

(ISO 14044:2006)
ENVIRONMENTAL MANAGEMENT -
- LIFE CYCLE ASSESSMENT --
REQUIREMENTS AND GUIDELINES
(2006)

(ISO 14025:2006)
ENVIRONMENTAL LABELS AND
DECLARATIONS-TYPE III
ENVIRONMENTAL DECLARATIONS-
PRINCIPLES AND PROCEDURES.
(2006)

GPI, GENERAL PROGRAMME
INSTRUCTIONS FOR THE
INTERNATIONAL EPD[®] SYSTEM V2.
5 (2015-05-11)

EN 15804:2012+A1,
SUSTAINABILITY OF
CONSTRUCTION WORKS.
ENVIRONMENTAL PRODUCT
DECLARATIONS. CORE RULES FOR
THE PRODUCT CATEGORY OF
CONSTRUCTION PRODUCTS
(2014).

PCR 2012:01, CONSTRUCTION
PRODUCTS AND CONSTRUCTION
SERVICES V2.1 (2017-01-04).




PCR 2015:04, UN CPC 4299,
4357, 4394, 4931, 4954,
FABRICATED PRODUCT MADE OUT
OF METAL COMPOSITE MATERIAL
(MCM) V1.0 (2015-08-19)

ALUCOIL, S.A.

C/ Ircio Parc. R72 a R77
Pol. Ind. De Bayas
09200 Miranda de Ebro
Burgos (SPAIN)




	<p>Summary</p> <p>Environmental Product Declaration</p>
<p>The International EPD® System</p>  <p>THE GREEN YARDSTICK</p> <p>www.environdec.com</p> <p>EPD International AB Box 210 60 SE-100 31 Stockholm Sweden</p>	<p>Program holder</p>
<p>Alucoil, S.A. C/ Ircio Parc. R72 a R77 Pol. Ind. De Bayas 09200 Miranda de Ebro Burgos (SPAIN) Tel: +34 947 333320 Fax: +34 947 324913 / +34 947 331224 www.alucoil.com</p>	 <p>Declaration holder</p>
<p>S-P-00363</p>	<p>Declaration number</p>
<p>Aluminum composite panel for use in architecture, automotive, naval and corporate image applications, among others,</p> <p>This declaration is an environmental product declaration according to ISO 14025 and EN 15804:2012+A1 and describes the specific environmental impacts of the building products mentioned. It is intended to foster the sustainable development of environmental and health friendly compatible construction.</p> <p>All relevant environmental data is contained in this validated declaration.</p> <p>The declaration is based on the PCR 2015:04 v1.0.</p>	<p>Declared Building Products</p>
<p>This validated declaration entitles the use of the label of the International EPD® System. This exclusively applies to the mentioned products; five years from the date of issue. The declaration holder is liable for the basic information and verifications.</p>	<p>Validity</p>
<p>This EPD is based on information modules that do not cover the aspects of use and end of life of the product. It contains in detail, for Module A1-A2-A3:</p> <ul style="list-style-type: none"> • Product definition and physical data • Information about raw materials and origin • Specifications on manufacturing the product • Notes on product processing • LCA based on a declared unit, cradle-to-gate • LCA results • Evidence and verifications 	<p>Content of the declaration</p>

			Summary Environmental Product Declaration																																
2014-05-14			Registration date																																
2017-03-15			Revision date																																
2022-03-15			Valid until																																
Lorena Pereda Pereda			Verifier appoint by EPD®System																																
																																			
Lorena Pereda Pereda External EPD Verifier		Raúl Mariscal Díaz de Sarralde Plant Manager-Alucoil, S.A.																																	
<p>larson pe® is a composite panel produced by two metal sheets (Aluminium) with a low density polyethylene inside core that lends flatness and lightness to the material.</p> <p>larson fr® is an innovative composite panel developed by Alucoil using two metal sheets (Aluminium), and a mineral core. The core delays combustion to achieve a B-S1, d0 classification according to the regulations UNE-EN 13501.</p> <p>In both products, the aluminium front sheet is coated of PVdF 70% Kynar 500 or similar, an anticorrosion pretreatment is included on top and reverse side. The aluminium back sheet is treated to provide the product with a regular and well attached layer which will protect it against corrosion and increase the adherence of the core.</p>			Product description																																
<p>larson® composite panels are advanced materials for building, transport and industry applications.</p> <p>larson pe® is especially recommended for new-construction ventilated facade sectors as well as restoration. It allows for ventilated, semi-ventilated or air-tight facades.</p> <p>larson fr® is the first step of a new composite panel generation with which Alucoil hopes to answer modern architectural needs.</p>			Applications																																
<p>The Life Cycle Assessment (LCA) was performed according to ISO 14040 ff. corresponding to the requirements of the guidelines concerning Type III declarations. Specific industrial data from Alucoil, S.A., data from the data base ecoinvent 3.2 and sector data from GDA (Gesamtverband der Aluminiumindustrie e.V (GDA) are used in this LCA.</p> <p>The method applied for assessment is CML-IA baseline v4.2 (April 2013) EU25, included in SimaPro software version 8.3.0.</p>			Scope of the LCA																																
<table border="1"> <thead> <tr> <th>Environmental Indicator</th> <th></th> <th>larson pe® A1-A3</th> <th>larson fr® A1-A3</th> </tr> </thead> <tbody> <tr> <td>Global warming (GWP100)</td> <td>kg CO2eq</td> <td>34.5</td> <td>36.9</td> </tr> <tr> <td>Ozone layer depletion (ODP)</td> <td>kg CFC-11eq</td> <td>1.02E-06</td> <td>1.29E-06</td> </tr> <tr> <td>Acidification (AP)</td> <td>kg SO2 eq</td> <td>0.169</td> <td>0.173</td> </tr> <tr> <td>Eutrophication (EP)</td> <td>kg PO4- eq</td> <td>0.0103</td> <td>0.0142</td> </tr> <tr> <td>Photochemical oxidation (POCP)</td> <td>kg C2H2 eq</td> <td>9.87E-03</td> <td>1.03E-03</td> </tr> <tr> <td>Abiotic depletion (elements)</td> <td>kg Sb eq</td> <td>1.49E-05</td> <td>1.46E-05</td> </tr> <tr> <td>Abiotic depletion (fossil)</td> <td>MJ</td> <td>521</td> <td>466</td> </tr> </tbody> </table>			Environmental Indicator		larson pe® A1-A3	larson fr® A1-A3	Global warming (GWP100)	kg CO2eq	34.5	36.9	Ozone layer depletion (ODP)	kg CFC-11eq	1.02E-06	1.29E-06	Acidification (AP)	kg SO2 eq	0.169	0.173	Eutrophication (EP)	kg PO4- eq	0.0103	0.0142	Photochemical oxidation (POCP)	kg C2H2 eq	9.87E-03	1.03E-03	Abiotic depletion (elements)	kg Sb eq	1.49E-05	1.46E-05	Abiotic depletion (fossil)	MJ	521	466	Results of the LCA
Environmental Indicator		larson pe® A1-A3	larson fr® A1-A3																																
Global warming (GWP100)	kg CO2eq	34.5	36.9																																
Ozone layer depletion (ODP)	kg CFC-11eq	1.02E-06	1.29E-06																																
Acidification (AP)	kg SO2 eq	0.169	0.173																																
Eutrophication (EP)	kg PO4- eq	0.0103	0.0142																																
Photochemical oxidation (POCP)	kg C2H2 eq	9.87E-03	1.03E-03																																
Abiotic depletion (elements)	kg Sb eq	1.49E-05	1.46E-05																																
Abiotic depletion (fossil)	MJ	521	466																																
Issued by: Alucoil, S.A.																																			
<p>The Environmental Product Declaration gives evidence of the validation of the used data. Data quality requirements are declared.</p> <p>Furthermore, specific applied chemical substances are declared in accordance with Regulation (EC) n° 1907/2006.</p>			Evidence and verifications																																



ENVIRONMENTAL PRODUCT DECLARATION

larson pe®-larson fr®



larson pe® larson fr®

ALUMINIUM COMPOSITE PANEL FOR ARCHITECTURAL SECTOR, CORPORATE DESIGN APPLICATIONS, AUTOMOTIVE AND NAVAL SECTOR, AMONG OTHERS



Publisher:
The Norwegian EPD Foundation
Registration number:
NEPD-1302-424-EN



epd-norge.no
The Norwegian EPD Foundation

According to

(ISO 14044:2006)
ENVIRONMENTAL MANAGEMENT -
- LIFE CYCLE ASSESSMENT --
REQUIREMENTS AND GUIDELINES
(2006)

(ISO 14025:2006)
ENVIRONMENTAL LABELS AND
DECLARATIONS-TYPE III
ENVIRONMENTAL DECLARATIONS-
PRINCIPLES AND PROCEDURES.
(2006)

GPI, GENERAL PROGRAMME
INSTRUCTIONS FOR THE
INTERNATIONAL EPD® SYSTEM
V2. 5 (2015-05-11)

EN 15804:2012+A1,
SUSTAINABILITY OF
CONSTRUCTION WORKS.
ENVIRONMENTAL PRODUCT
DECLARATIONS. CORE RULES FOR
THE PRODUCT CATEGORY OF
CONSTRUCTION PRODUCTS
(2014).

PCR 2012:01, CONSTRUCTION
PRODUCTS AND CONSTRUCTION
SERVICES V2.1 (2017-01-04).

PCR 2015:04, UN CPC 4299,
4357, 4394, 4931, 4954,
FABRICATED PRODUCT MADE OUT
OF METAL COMPOSITE MATERIAL
(MCM) V1.0 (2015-08-19)

ALUCOIL, S.A.

C/ Ircio Parc. R72 - R77
Pol. Ind. de Bayas
09200 Miranda de Ebro
Burgos (SPAIN)



	<p>Summary</p> <p>Environmental Product Declaration</p>
<p>The International EPD® System</p>	<p>Program holder</p>
<p>Alucoil, S.A. C/ Ircio Parc. R72 - R77 Pol. Ind. de Bayas 09200 Miranda de Ebro Burgos (SPAIN) Tel: +34 947 333320 Fax: +34 947 324913 / +34 947 331224 www.alucoil.com</p>	<p>Declaration holder</p>
<p>S-P-00363</p> <p>Aluminium composite panel for use in architecture, automotive, naval and corporate image applications, among others,</p> <p>This declaration is an environmental product declaration according to ISO 14025 and EN 15804:2012+A1 and describes the specific environmental impacts of the building products mentioned. It is intended to foster the sustainable development of environmental and health friendly compatible construction.</p> <p>All relevant environmental data is contained in this validated declaration.</p> <p>The declaration is based on the PCR 2015:04 v1.0.</p>	<p>Declaration number</p> <p>Declared building products</p>
<p>This validated declaration entitles the use of the logotype of the International EPD® System. This exclusively applies to the mentioned products; five years from the date of issue. The declaration holder is liable for the basic information and verifications.</p>	<p>Validity</p>
<p>This EPD is based on information modules that do not cover the aspects of use and end of life of the product. It contains in detail, for Module A1-A2-A3:</p> <ul style="list-style-type: none"> • Product definition and physical data • Information about raw materials and origin • Specifications on manufacturing the product • Notes on product processing • LCA based on a declared unit, cradle-to-gate • LCA results • Evidence and verifications 	<p>Content of the declaration</p>






THE GREEN YARDSTICK

www.environdec.com

EPD International AB
Box 210 60 SE-100 31 Stockholm
Sweden



	<p style="text-align: right;">Summary</p> <p style="text-align: center;">Environmental Product Declaration</p>																																
2014-05-14	Registration date																																
2017-03-15	Revision date																																
2022-03-15	Valid until																																
Lorena Pereda Pereda	Verifier appointed by EPD®System																																
<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  Lorena Pereda Pereda External EPD Verifier </div> <div style="text-align: center;">  Raúl Mariscal Díaz de Sarralde Plant Manager-Alucoil, S.A. </div> </div>	Signatures																																
<p>larson pe® is a composite panel produced by two metal sheets (Aluminium) with a low density polyethylene inside core that lends flatness and lightness to the material.</p> <p>larson fr® is an innovative composite panel developed by Alucoil using two metal sheets (Aluminium), and a mineral core. The core delays combustion to achieve a B-S1, d0 classification according to the regulations UNE-EN 13501.</p> <p>In both products, the aluminium front sheet is coated of PVdF 70% Kynar 500 or similar, an anticorrosion pretreatment is included on top and reverse side. The aluminium back sheet is treated to provide the product with a regular and well attached layer which will protect it against corrosion and increase the adherence of the core.</p>	Product description																																
<p>larson® composite panels are advanced materials for building, transport and industry applications.</p> <p>larson pe® is especially recommended for new-construction ventilated facade sectors as well as restoration. It allows for ventilated, semi-ventilated or air-tight facades.</p> <p>larson fr® is the first step of a new composite panel generation with which Alucoil hopes to answer modern architectural needs.</p>	Applications																																
<p>The Life Cycle Assessment (LCA) was performed according to ISO 14040 ff. corresponding to the requirements of the guidelines concerning Type III declarations. Specific industrial data from Alucoil, S.A., data from the data base ecoinvent 3.2 and sector data from GDA (Gesamtverband der Aluminiumindustrie e.V (GDA) are used in this LCA.</p> <p>The method applied for assessment is CML-IA baseline v4.2 (April 2013) EU25, included in SimaPro software version 8.3.0.</p>	Scope of the LCA																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Environmental Indicator</th> <th></th> <th style="text-align: center;">larson pe® A1-A3</th> <th style="text-align: center;">larson fr® A1-A3</th> </tr> </thead> <tbody> <tr> <td>Global warming (GWP100)</td> <td>kg CO2 eq</td> <td style="text-align: center;">34.5</td> <td style="text-align: center;">36.9</td> </tr> <tr> <td>Ozone layer depletion (ODP)</td> <td>kg CFC-11 eq</td> <td style="text-align: center;">1.02E-06</td> <td style="text-align: center;">1.29E-06</td> </tr> <tr> <td>Acidification (AP)</td> <td>kg SO2 eq</td> <td style="text-align: center;">0.169</td> <td style="text-align: center;">0.173</td> </tr> <tr> <td>Eutrophication (EP)</td> <td>kg PO4- eq</td> <td style="text-align: center;">0.0103</td> <td style="text-align: center;">0.0142</td> </tr> <tr> <td>Photochemical oxidation (POCP)</td> <td>kg C2H2 eq</td> <td style="text-align: center;">9.87E-03</td> <td style="text-align: center;">1.03E-03</td> </tr> <tr> <td>Abiotic depletion (elements)</td> <td>kg Sb eq</td> <td style="text-align: center;">1.49E-05</td> <td style="text-align: center;">1.46E-05</td> </tr> <tr> <td>Abiotic depletion (fossil)</td> <td>MJ</td> <td style="text-align: center;">521</td> <td style="text-align: center;">466</td> </tr> </tbody> </table>	Environmental Indicator		larson pe® A1-A3	larson fr® A1-A3	Global warming (GWP100)	kg CO2 eq	34.5	36.9	Ozone layer depletion (ODP)	kg CFC-11 eq	1.02E-06	1.29E-06	Acidification (AP)	kg SO2 eq	0.169	0.173	Eutrophication (EP)	kg PO4- eq	0.0103	0.0142	Photochemical oxidation (POCP)	kg C2H2 eq	9.87E-03	1.03E-03	Abiotic depletion (elements)	kg Sb eq	1.49E-05	1.46E-05	Abiotic depletion (fossil)	MJ	521	466	Results of the LCA
Environmental Indicator		larson pe® A1-A3	larson fr® A1-A3																														
Global warming (GWP100)	kg CO2 eq	34.5	36.9																														
Ozone layer depletion (ODP)	kg CFC-11 eq	1.02E-06	1.29E-06																														
Acidification (AP)	kg SO2 eq	0.169	0.173																														
Eutrophication (EP)	kg PO4- eq	0.0103	0.0142																														
Photochemical oxidation (POCP)	kg C2H2 eq	9.87E-03	1.03E-03																														
Abiotic depletion (elements)	kg Sb eq	1.49E-05	1.46E-05																														
Abiotic depletion (fossil)	MJ	521	466																														
Issued by: Alucoil, S.A.																																	
<p>The Environmental Product Declaration gives evidence of the validation of the used data. Data quality requirements are declared.</p> <p>Furthermore, specific applied chemical substances are declared in accordance with Regulation (EC) n° 1907/2006.</p>	Evidence and verifications																																